

# Crepe tapes

Self-adhesive paper tape with solvent adhesive suitable for protection. Its properties make it widely applicable in different professional fields such as painting, lacquer – and construction works:

- ✓ High immediate tack on different surfaces
  - ✓ No removal marks
  - ✓ High heat resistance

## Properties

- High adhesion power
- Recyclable
- Easy to remove and leaves no traces on surfaces
- Resistant to high temperatures – up to app. 60°C/90 minutes; app. 80°C/60 minutes
- Resistant to low temperatures – up to app. -20°C



	60°C	80°C	120°C
Total thickness	125my +/-10%	135my +/-10%	135my +/-10%
Carrier thickness	60my +/-10%	60my +/-10%	70my +/-10%
Adhesive application	60g/m <sup>2</sup> +/-10%	60g/m <sup>2</sup> +/-10%	65g/m <sup>2</sup> +/-10%
Adhesion power	2,3N/cm +/-10%	2,7N/cm +/-10%	2,9N/cm +/-10%
Tensile strength	9%	9%	10%
Max. length	500mtr	500mtr	500mtr
Max. width	300mm	300mm	300mm
Colors	yellow	yellow	white
Cold edurance	up to -20°C	up to -20°C	up to -20°C
Heat edurance	up to 60°C	up to 60°C during 90 min up to 80°C during 60 min.	up to 80°C during 90 min. up to 120°C during 60 min.

Dimensions	Packing/ articles
19mm x 50m	64
25mm x 50m	48
30mm x 50m	40
38mm x 50m	32
50mm x 50m	24